

AW 708 - Specificații tehnice

Descriere

AW 708 a fost dezvoltată pentru cultivarea solului, transport și recoltarea fânului cu utilaje, remorci și prese de balotat. Este disponibilă o versiune HD cu un compus special rezistent la tăiere și așchiere.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Remorcă
Industrial: Remorcă



| | |
|-----------------------|-------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 500/65 - 17 |
| LI/SS FREE ROLLING | 160 A8 |

Dimensiuni US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94034307 |
| Rating de sarcină | 18 |
| Lățimea secțiunii (inch) | 20.7 |
| Overall Diameter (inch) | 42.5 |
| Static Loaded Radius (inch) | 18.2 |
| Rolling Circumference (inch) | 123.4 |
| Rim Rec | 16.0 |
| ECE | E11-106R-004549 |

Load capacity (lbs)

| mph / psi | 51 |
|-----------|-------|
| 5 FR | 13890 |
| 15 FR | 11810 |
| 20 FR | 11110 |
| 25 FR | 9920 |

Imprimat pe 4/24/2024 7:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..