

## AW 708 - Specificații tehnice

### Descriere

AW 708 a fost dezvoltată pentru cultivarea solului, transport și recoltarea fânului cu utilaje, remorci și prese de balotat. Este disponibilă o versiune HD cu un compus special rezistent la tăiere și așchiere.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Presă de balotat • Mașini de implementare •  
Remorcă  
Industrial: Remorcă



Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	520/50 - 17
LI/SS FREE ROLLING	162 A8

## Dimensiuni US Standard

Usa code	94063413
Lățimea secțiunii (inch)	20.3
Overall Diameter (inch)	37.5
Static Loaded Radius (inch)	15.9
Rolling Circumference (inch)	109.3
Rim Rec	16.00
ECE	E11-106R-005852

## Load capacity (lbs)

mph / psi	58
5 FR	14660
15 FR	12465
20 FR	11730
25 FR	10470

Imprimat pe 4/24/2024 3:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..