

## AW 726 - Specificații tehnice



### Descriere

AW 726 a fost special concepută pentru remorci în operațiuni de transport. Este optimă atât pentru utilizarea pe drum, cât și off-road. AW 726 prezintă performanțe excelente pe drum și caracteristici de auto-curățare. Designul tip bloc oferă un ciclu de viață extins al anvelopei.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Remorcă

Versiune	ARAMID BELTED
Tip	TL
Dimensiunea anvelopei	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

## Dimensiuni US Standard

Usa code	94064366
Rating de sarcină	14
Lățimea secțiunii (inch)	11.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	14.3
Rolling Circumference (inch)	99.6
Rim Rec	9.00
ECE	E11-106R-0010913

## Load capacity (lbs)

mph / psi	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/13/2025 8:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..