

## AW 726 - Specificații tehnice



### Descriere

AW 726 a fost special concepută pentru remorci în operațiuni de transport. Este optimă atât pentru utilizarea pe drum, cât și off-road. AW 726 prezintă performanțe excelente pe drum și caracteristici de auto-curățare. Designul tip bloc oferă un ciclu de viață extins al anvelopei.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Remorcă

Versiune	STEEL BELTED
Tip	TL
Dimensiunea anvelopei	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

## Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	300
Overall Diameter (mm)	855
Static Loaded Radius (mm)	373
Rolling Circumference (mm)	2540
Rim Rec	9.00
ECE	E11-106R-006974

## Load capacity (Kg)

km/h / bar	4.80
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430
10 DW	2380
25 DW	2025
30 DW	1905
40 DW	1700

Imprimat pe 4/20/2024 3:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..