

BK 627 - Specificații tehnice



Descriere

BK 627 este o anvelopă cu model bloc, potrivită pentru transport și operațiuni de cultivare a solului cu remorci și utilaje. Este destinată în principal deplasării pe câmp și este ideală pentru condiții dificile.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare • Tractor • Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	7.50 - 16
LI/SS	121 A8

Dimensiuni US Standard

Usa code	94041183
Rating de sarcină	12
Lățimea secțiunii (inch)	8.7
Overall Diameter (inch)	31.9
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	98.2
Rim Rec	6.0
ECE	E11-106R-004256

Load capacity (lbs)

mph / psi	74
25	3200

Imprimat pe 4/23/2024 7:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..