

BK 823 - Specificații tehnice



Descriere

BK 823 este o anvelopă concepută pentru tractoare, utilaje și remorci, utilizată în principal în aplicații de cultivare a solului și de transport atât pe câmp, cât și pe șosea. Modelul său special cu blocuri face ca anvelopa să fie potrivită mai ales pentru lucrări în condiții grele unde este necesară o performanță excelentă de direcție. Este disponibilă și o versiune HD cu rezistență îmbunătățită la tăiere și așchiere.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare • Tractor • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	9.00 - 16
LI/SS	121 A8

Dimensiuni Standard internațional

Rating de sarcină	10
Lățimea secțiunii (mm)	245
Overall Diameter (mm)	891
Static Loaded Radius (mm)	394
Rolling Circumference (mm)	2583
Rim Rec	6.5

Load capacity (Kg)

km/h / bar	3.20
40	1450

Imprimat pe 4/28/2024 1:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..