

BK 826 - Specificații tehnice



Descriere

BK 826 a fost special concepută pentru remorci în aplicații de transport. Este o anvelopă înclinată cu o capacitate mare de încărcare datorită carcasi sale ranforsate. BK 826 este, de asemenea, disponibilă în versiunea "industrială" care prezintă o rezistență deosebită la tăiere și așchiere și este potrivită și pentru buldoexcavatoare.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Remorcă

Industrial: Buldoexcavator • Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	8.25 - 16

Dimensiuni US Standard

Usa code	94034475
Rating de sarcină	18
Lățimea secțiunii (inch)	9.4
Overall Diameter (inch)	34
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E4-54R-0024097

Load capacity (lbs)

mph / psi	115
62 LS	4190
62 LD	3970

Imprimat pe 4/24/2024 5:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..