

## BK 826 - Specificații tehnice



### Descriere

BK 826 a fost special concepută pentru remorci în aplicații de transport. Este o anvelopă înclinată cu o capacitate mare de încărcare datorită carcasei sale ranforsate. BK 826 este, de asemenea, disponibilă în versiunea "industrială" care prezintă o rezistență deosebită la tăiere și așchiere și este potrivită și pentru buldoexcavatoare.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Remorcă

Industrial: Buldoexcavator • Remorcă

Versiune	TRACTOR TRAILER
Tip	TT
Dimensiunea anvelopei	9.00 - 16
LI/SS	138 A6

## Dimensiuni US Standard

Usa code	94047017
Rating de sarcină	18
Lățimea secțiunii (inch)	10.4
Overall Diameter (inch)	36.4
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-005356

## Load capacity (lbs)

mph / psi	110
20	5200

Imprimat pe 4/24/2024 10:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..