BK 826 - Specificații tehnice

Descriere

Anvelopa BK 826 este proiectată de experți pentru remorci în aplicații de transport, oferind durabilitate și performanță de neegalat. Versiunea „Harvester Special" este adaptată special pentru recoltare, asigurând o fiabilitate optimă pe teren. Această anvelopă cu cută înclinată are o carcasă ranforsată, oferind o capacitate de încărcare excepțională pentru a satisface cerințele sarcinilor dificile. În plus, modelul BK 826 este disponibil într-o variantă „industrială", proiectată cu o rezistență superioară la tăiere și așchiere, ceea ce o face alegerea ideală pentru retroexcavatoare în condiții dificile.

UM

US Standard

Construcție

BIAS

Mașinării

Agricultură: Mașină de recoltare • Remorcă
Industrial: Buldoexcavator • Remorcă

Versiune	TRACTOR TRAILER
Tip	TT
Dimensiunea anvelopei	9.00 - 16
LI/SS	138 A8

Dimensiuni US Standard

Usa code	94062164
Rating de sarcină	18
Lățimea secțiunii (inch)	10.4
Overall Diameter (inch)	36.4
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	110
20	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/12/2024 8:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..