

COMMANDER (R) - Specificații tehnice



Descriere

COMMANDER (R) este o anvelopă agricolă cu o banda de rulare adâncă, cu baze puternice pentru caneluri, pentru un ciclu de viață mai lung. Designul special cu unghi dublu oferă tracțiune excelentă în câmp și proprietăți de autocurățare superioare. Carcasa puternică este realizată dintr-un compus rezistent la tăiere și așchiere, oferind o rezistență mai bună la perforare împreună cu o capacitate mare de încărcare. COMMANDER (R) este anvelopa perfectă pentru operațiunile de cultivare a solului, transport și recoltare.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Mașină de recoltare • Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.4 - 24
LI/SS	121 A6

Dimensiuni Standard internațional

Rating de sarcină	8
TKPH	1
Lățimea secțiunii (mm)	328
Overall Diameter (mm)	1180
Static Loaded Radius (mm)	569
Rolling Circumference (mm)	3669
Rim Rec	W 11
Rim Alt	W 10
ECE	E11-106R-005208
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	1450

Imprimat pe 9/16/2024 11:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..