

## CON STAR - Specificații tehnice



### Descriere

CON STAR este potrivită mai ales pentru încărcătoare compacte și manipolatoare telescopice în aplicații agroindustriale, de ridicare și încărcare. Are o tracțiune excelentă și o stabilitate verticală și orizontală excelentă. CON STAR a fost realizată dintr-un compus rezistent la tăiere și așchiere, care contribuie la un ciclu de viață extins al anvelopei.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Încărcător compact • Încărcător telescopic  
Industrial: Încărcător compact • Încărcător telescopic

Versiune	INDUSTRIAL
Tip	TL
Dimensiunea anvelopei	500/70 - 24 (19.5L - 24)
LI/SS	164 A8

## Dimensiuni Standard internațional

Lățimea secțiunii (mm)	505
Overall Diameter (mm)	1300
Static Loaded Radius (mm)	579
Rolling Circumference (mm)	3926
SRI (mm)	625
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E11-106R-003031

## Load capacity (Kg)

km/h / bar	4.00
40	5000

Imprimat pe 4/24/2024 6:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..