

CONTAINER KING - Specificații tehnice



Descriere

CONTAINER KING a fost proiectată pentru stivuitoare în transport intermodal și aplicații logistice. Această anvelopă extraordinară este fabricată dintr-un compus al benzii de rulare foarte rezistent la uzură, care minimizează crăpăturile benzii de rulare. CONTAINER KING asigură un ciclu de viață extins al anvelopei plus stabilitate excepțională în modul de ridicare.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Stivuior de containere

Versiune	INDUSTRIAL
Tip	TL
Dimensiunea anvelopei	18.00 - 25

Dimensiuni Standard internațional

Rating de sarcină	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	22950

Imprimat pe 4/29/2024 5:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..