

EARTHMAX CRUSHER HAUL - Specificații tehnice



Descriere

EARTHMAX CRUSHER HAUL este o anvelopă radială cu structură din oțel concepută pentru aplicații de transport, atât pe șosea, cât și în afara acesteia, precum și pentru operațiuni miniere. Are durabilitate și kilometraj îmbunătățite și o capacitate mare de încărcare datorită construcției și carcasi puternice și curelelor din oțel. Modelul benzii de rulare tip bloc oferă o tracțiune excelentă. În plus, EARTHMAX CRUSHER HAUL asigură un confort excelent la condus, mai puțină oboseală la condus și o manevrabilitate superioară.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

OTR: Camion On/Off

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	10.00 R 20
LI/SS	149/146 J

Dimensiuni Standard internațional

Rating de sarcină	18
Overall Width (mm)	272
Overall Diameter (mm)	1065
Rim Rec	7.50
Rim Alt	8.00

Load capacity (Kg)

km/h / bar	8.30
100 Load Single	3250
100 Load Dual	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 12/9/2024 11:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..