

## EARTHMAX SR 30 - Specificații tehnice



### Descriere

EARTHMAX SR 30 (E-3/L-3) este o anvelopă radială cu structură din oțel cu dublă utilizare pentru încărcătoare și basculante articulate. Curelele de oțel cu straturi multiple și modelul bloc rigid asigură tracțiune, stabilitate și durabilitate excelente. Compusul special rezistent la tăiere face din EARTHMAX SR 30 soluția ideală pentru o varietate de condiții de operare dificile.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

OTR: Basculantă articulată (ADT) • Buldozer • Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	17.5 R 25
LI/SS	188 A2

## Dimensiuni US Standard

Usa code	94066315
Overall Width (inch)	17.6
Overall Diameter (inch)	53
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	158.3
Rim Rec	14.00/1.5
Star Rating	***
TRA Code	L3

## Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	19300	19800	20400	20900	21500	22000

Imprimat pe 4/27/2024 6:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..