

## EARTHMAX SR 30 - Specificații tehnice



### Descriere

EARTHMAX SR 30 (E-3/L-3) este o anvelopă radială cu structură din oțel cu dublă utilizare pentru încărcătoare și basculante articulate. Curelele de oțel cu straturi multiple și modelul bloc rigid asigură tracțiune, stabilitate și durabilitate excelente. Compusul special rezistent la tăiere face din EARTHMAX SR 30 soluția ideală pentru o varietate de condiții de operare dificile.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

OTR: Basculantă articulată (ADT) • Buldozer • Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	29.5 R 25
LI/SS	200 B/208 A2

## Dimensiuni US Standard

Usa code	94034291
TMPH	185
Overall Width (inch)	30.1
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.7
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Imprimat pe 4/27/2024 10:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..