

## EARTHMAX SR 30 - Fișa de date



### Descriere

EARTHMAX SR 30 (E-3/L-3) este o anvelopă radială cu structură din oțel cu dublă utilizare pentru încărcătoare și basculante articulate. Curelele de oțel cu straturi multiple și modelul bloc rigid asigură tracțiune, stabilitate și durabilitate excelente. Compusul special rezistent la tăiere face din EARTHMAX SR 30 soluția ideală pentru o varietate de condiții de operare dificile.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

OTR: Basculantă articulată (ADT) • Buldozer • Încărcător

| SIZE      | Version                | TRA Code | Star R | LI/SS        | RIM REC   | RIM ALT   | OW  | OD   | SLR | RC   | Type | TKPH |
|-----------|------------------------|----------|--------|--------------|-----------|-----------|-----|------|-----|------|------|------|
| 15.5 R 25 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 160 B/169 A2 | 12.00/1.3 | -         | 397 | 1276 | 574 | 3809 | TL   | 130  |
| 17.5 R 25 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 167 B/176 A2 | 14.00/1.5 |           | 446 | 1347 | 606 | 4021 | TL   | 150  |
| 17.5 R 25 | CUT RESISTANT COMPOUND | L3       | ***    | 188 A2       | 14.00/1.5 |           | 446 | 1347 | 606 | 4021 | TL   |      |
| 20.5 R 25 | CUT RESISTANT COMPOUND | L3       | **     | 193 A2       | 17.00/2.0 | 17.00/1.7 | 529 | 1487 | 663 | 4439 | TL   |      |
| 20.5 R 25 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 177 B/186 A2 | 17.00/2.0 | 17.00/1.7 | 529 | 1487 | 663 | 4439 | TL   | 170  |
| 23.5 R 25 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 185 B/195 A2 | 19.50/2.5 |           | 612 | 1607 | 711 | 4797 | TL   | 200  |
| 26.5 R 25 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 193 B/202 A2 | 22.00/3.0 |           | 689 | 1742 | 766 | 5200 | TL   | 230  |
| 26.5 R 25 | CUT RESISTANT COMPOUND | E3       | **     | 193 B        | 22.00/3.0 |           | 689 | 1742 | 766 | 5200 | TL   | 230  |
| 26.5 R 25 | CUT RESISTANT COMPOUND | L3       | *      | 202 A2       | 22.00/3.0 |           | 689 | 1742 | 766 | 5200 | TL   |      |
| 29.5 R 25 | CUT RESISTANT COMPOUND | E3/L3    | **/*   | 200 B/208 A2 | 25.00/3.5 |           | 765 | 1861 | 818 | 5555 | TL   | 270  |
| 29.5 R 25 | CUT RESISTANT COMPOUND | L3       | *      | 208 A2       | 25.00/3.5 |           | 765 | 1861 | 818 | 5555 | TL   |      |
| 29.5 R 25 | CUT RESISTANT COMPOUND | E3       | **     | 200 B        | 25.00/3.5 |           | 765 | 1861 | 818 | 5555 | TL   | 270  |

Imprimat pe 4/27/2024 9:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..