

EARTHMAX SR 315 - Specificații tehnice



Descriere

EARTHMAX SR 315 este o anvelopă radială cu structură din oțel special concepută și proiectată pentru bascularea încărcăturilor. Oferă performanțe excelente în operațiunile de săpat, încărcare și încărcare și transport în minele subterane.

Este echipată cu o carcasă puternică, întărită cu mai multe curele de oțel, care minimizează ruperea prin impact și perforarea cauzată de pietre. Pereții laterali și zonele de sprijin ranforsate EARTHMAX SR 315 garantează performanțe excelente în zone extrem de stâncoase, minimizând tăieturile de rocă și deteriorările cauzate de spălare. Banda de rulare netedă L-3S reduce găurirea cauzată de roci și piatră.

Compusul EARTHMAX SR 315 este proiectat special pentru a asigura o generare scăzută de căldură și fiabilitate în serviciile miniere subterane (UMS).

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Basculare încărcături (LHD)

| | |
|-----------------------|------------------------|
| Versiune | CUT RESISTANT COMPOUND |
| Tip | TL |
| Dimensiunea anvelopei | 26.5 R 29 |
| LI/SS | 217 A2 |

Dimensiuni US Standard

| | |
|------------------------------|-----------|
| Usa code | 94070787 |
| Overall Width (inch) | 28.5 |
| Overall Diameter (inch) | 73.4 |
| Static Loaded Radius (inch) | 32.7 |
| Rolling Circumference (inch) | 221.9 |
| Rim Rec | 22.00/3.0 |
| Star Rating | *** |
| TRA Code | L3S |

Load capacity (lbs)

| mph / psi | 98 | 102 | 105 | 109 | 112 | 116 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 44100 | 45400 | 46700 | 48100 | 49400 | 50700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 12/7/2024 9:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..