

EARTHMAX SR 315 - Fișa de date



Descriere

EARTHMAX SR 315 este o anvelopă radială cu structură din oțel special concepută și proiectată pentru bascularea încărcăturilor. Oferă performanțe excelente în operațiunile de săpat, încărcare și încărcare și transport în minele subterane.

Este echipată cu o carcasă puternică, întărită cu mai multe curele de oțel, care minimizează ruperea prin impact și perforarea cauzată de pietre. Pereții laterali și zonele de sprijin ranforsate EARTHMAX SR 315 garantează performanțe excelente în zone extrem de stâncoase, minimizând tăieturile de rocă și deteriorările cauzate de spălare. Banda de rulare netedă L-3S reduce găurirea cauzată de roci și piatră.

Compusul EARTHMAX SR 315 este proiectat special pentru a asigura o generare scăzută de căldură și fiabilitate în serviciile miniere subterane (UMS).

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Basculare încărcături (LHD)

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 R 29	CUT RESISTANT COMPOUND	94067411	L3S	**	211 A2	22.00/3.0		28.5	73.4	32.7	221.9	TL
26.5 R 29	CUT RESISTANT COMPOUND	94070787	L3S	***	217 A2	22.00/3.0		28.5	73.4	32.7	221.9	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 12/7/2024 10:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..