

EARTHMAX SR 31 - Specificații tehnice



Descriere

EARTHMAX SR 31 este o anvelopă radială cu structură din oțel special concepută pentru basculante articulate și încărcătoare frontale. Centurile sale din oțel cu straturi multiple oferă o rezistență și stabilitate extraordinare, în timp ce modelul blocului rigid nedirecțional oferă tracțiune și manevrabilitate excelente, chiar și pe terenuri noroioase. Pe lângă confortul remarcabil la condus, EARTHMAX SR 31 are un compus special al benzii de rulare, care este deosebit de rezistent la tăiere și la căldură. Structura carcasi radiale oferă, de asemenea, rezistență redusă la rulare, oferind economii semnificative de combustibil.

UM

US Standard

Construcție

 RADIAL

Mașinării

Industrial: Buldozer • Încărcător

OTR: Basculantă articulată (ADT) • Buldozer • Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	26.5 R 25
LI/SS	193 B/202 A2

Dimensiuni US Standard

Usa code	94053735
TMPH	158
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400
5	28300	29100	30900	32000	33100	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/15/2024 2:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..