

EARTHMAX SR 33 - Specificații tehnice



Descriere

Earthmax SR 33 este o anvelopă radială pentru camioane multifuncționale. Modelul benzii de rulare cu mai multe blocuri a fost special conceput pentru a garanta o tracțiune extraordinară pe suprafețe moi, nisipoase sau noroioase. Earthmax SR 33 oferă o stabilitate remarcabilă, pe lângă cele mai bune proprietăți de auto-curățare. Carcasa puternică cu structură din oțel are o durabilitate excelentă și rezistență la agățare și perforare.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	365/80 R 20 (14.5 R 20)
LI/SS	152 K

Dimensiuni Standard international

Overall Width (mm)	360
Overall Diameter (mm)	1096
Static Loaded Radius (mm)	496
Rolling Circumference (mm)	3318
Rim Rec	11
ECE	E11-54R-0017314

Load capacity (Kg)

km/h / bar	6.20
110	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/9/2025 7:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..