

## EARTHMAX SR 33 - Specificații tehnice



### Descriere

Earthmax SR 33 este o anvelopă radială pentru camioane multifuncționale. Modelul benzii de rulare cu mai multe blocuri a fost special conceput pentru a garanta o tracțiune extraordinară pe suprafețe moi, nisipoase sau noroioase. Earthmax SR 33 oferă o stabilitate remarcabilă, pe lângă cele mai bune proprietăți de auto-curățare. Carcasa puternică cu structură din oțel are o durabilitate excelentă și rezistență la agățare și perforare.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	395/85 R 20
LI/SS	168 J

## Dimensiuni US Standard

Usa code	94050611
Overall Width (inch)	15.5
Overall Diameter (inch)	46.6
Static Loaded Radius (inch)	21.2
Rolling Circumference (inch)	141.3
Rim Rec	10.00W
Rim Alt	10.00HF
ECE	E11-54R-0017315

## Load capacity (lbs)

mph / psi	125
62	12300

Imprimat pe 4/20/2024 8:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..