

EARTHMAX SR 34 - Specificații tehnice



Descriere

ARTHMAX SR 34 is an All Steel radial tire specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. EARTHMAX SR 34 is ideal for handling heavy loads. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under the most heavy-duty service conditions.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	16.00 R 25
LI/SS	177 B

Dimensiuni US Standard

Usa code	94070732
TMPH	130
Overall Width (inch)	17.3
Overall Diameter (inch)	59.4
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	180.1
Rim Rec	11.25/2.0
Star Rating	**
TRA Code	E3+

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	12300	12800	13200	13900	14300	14800	15200	15700	16100

Imprimat pe 5/4/2024 9:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..