

## EARTHMAX SR 412 - Specificații tehnice



### Descriere

EARTHMAX SR 412 (E-4/L-4) este o anvelopă radială cu structură din oțel special concepută pentru basculante articulate, încărcătoare și buldozere. Modelul unic al benzii de rulare E-4 asigură o tracțiune excelentă și o rezistență excepțională la căldură. Datorită carcasi și curelelor sale puternice din oțel, EARTHMAX SR 412 poate transporta sarcini grele, oferind o stabilitate excelentă, precum și cea mai bună rezistență la rupturi și perforări. EARTHMAX SR 412 are un design de muchie pătrată care maximizează contactul cu solul pentru o manevrabilitate excelentă.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

OTR: Basculantă articulată (ADT) • Buldozer • Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	750/65 R 25 (30/65 R 25)
LI/SS	190 B/202 A2

## Dimensiuni US Standard

Usa code	94065233
TMPH	157
Overall Width (inch)	30.7
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	190.5
Rim Rec	24.00/3.0
Rim Alt	22.00/3.0, 25.00/3.0
Star Rating	**/*
TRA Code	E4/L4

## Load capacity (lbs)

mph / psi	58	62	65	69
30	20900	21500	22700	23400
5	29100	30900	32000	33100

Imprimat pe 9/15/2024 6:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..