

EARTHMAX SR 412 - Fișa de date



Descriere

EARTHMAX SR 412 (E-4/L-4) este o anvelopă radială cu structură din oțel special concepută pentru basculante articulate, încărcătoare și buldozere. Modelul unic al benzii de rulare E-4 asigură o tracțiune excelentă și o rezistență excepțională la căldură. Datorită carcasei și curelelor sale puternice din oțel, EARTHMAX SR 412 poate transporta sarcini grele, oferind o stabilitate excelentă, precum și cea mai bună rezistență la rupturi și perforări. EARTHMAX SR 412 are un design de muchie pătrată care maximizează contactul cu solul pentru o manevrabilitate excelentă.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

OTR: Basculantă articulată (ADT) • Buldozer • Încărcător

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
29.5 R 25	CUT RESISTANT COMPOUND	E4	**	200 B	25.00/3.5		765	1865	834	5543	TL	252
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E4/L4	**/*	190 B/202 A2	24.00/3.0	22.00/3.0; 25.00/3.0	780	1602	715	4838	TL	229
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	E4	**	190 B	24.00/3.0	22.00/3.0; 25.00/3.0	780	1602	715	4838	TL	229
800/65 R 29	CUT RESISTANT COMPOUND	E4/L4	**/*	198 B / 208 A2	27.00/3.0	24.00/3.5 , 25.00/3.5	790	1805	825	5490	TL	206

Imprimat pe 4/26/2024 8:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..