

## EARTHMAX SR 431 - Specificații tehnice



### Descriere

EARTHMAX SR 431 (E-4) este o anvelopă cu structură din oțel special concepută pentru camioanele rigide care operează în condiții miniere dificile (mine de suprafață și subterane). Modelul nedirecțional al benzii de rulare asigură tracțiune și stabilitate excelente. Anvelopa are o carcasă solidă din oțel și un compus special al benzii de rulare care oferă o rezistență extraordinară la tăiere și așchiere, precum și o durată lungă de viață chiar și în medii stâncoase, abrazive și dure.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	16.00 R 25
LI/SS	177 B

## Dimensiuni US Standard

Usa code	94062386
TMPH	114
Overall Width (inch)	17.8
Overall Diameter (inch)	60.3
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	183
Rim Rec	11.25/2.0
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	12300	12800	13200	13900	14300	14800	15200	15700	16100

Imprimat pe 2/22/2024 10:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..