

EARTHMAX SR 44 - Fișa de date



Descriere

EARTHMAX SR 44 este o anvelopă radială cu structură din oțel potrivită pentru o varietate de aplicații, inclusiv aplicații de minerit, transport și exploatare forestieră. Modelul E-4 al benzii de rulare asigură o tracțiune excelentă și un confort superior al operatorului. EARTHMAX SR 44 (E-4) este capabilă să optimizeze productivitatea indiferent de operațiune.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

OTR: Camion On/Off

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH	ECE
7.50 R 16	STANDARD			122/118 G	6	5.5, 6.5	226	820	380	2450	TT		
10.00 R 20	STANDARD			146/143 G	7.50	7.0 ; 7.50VM ; 8.0	268	1075	505	3200	TT		E11-54R-0015908
11.00 R 20	STANDARD	E4	***		8.00	7.50 ; 8.50;8.50VM	282	1111	520	3328	TT		
12.00 R 20	STANDARD	E4	***		8.50V	9.00V	305	1138	532	3408	TT		
12.00 R 24 (325/95 R 24)	STANDARD	E4	***	158 B	8.50V	9.00V	310	1250	575	3790	TT	140	
325/95 R 24 (12.00 R 24)	STANDARD	E4	***	158 B	8.50V	9.00V	310	1250	575	3790	TT	140	
325/95 R 24 (12.00 R 24)	STANDARD	E4	***	158 B	8.50V	9.00V	310	1250	575	3790	TL	140	

Imprimat pe 4/26/2024 7:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..