

EARTHMAX SR 45 H2 - Specificații tehnice



Descriere

EARTHMAX SR 45 H2 este o anvelopă radială cu structură din oțel special concepută pentru camioanele de transport rigide. Adâncimea benzii de rulare E-4 și modelul unic al benzii de rulare asigură o uzură excelentă, minimizând vibrațiile și zgomotul. EARTHMAX SR 45 H2 este ideală pentru toate operațiunile care necesită tracțiune și stabilitate. Carcasa din oțel oferă o rezistență excelentă la rupturi și perforări și o durată lungă de viață. Disponibilă în compuși standard, rezistenți la căldură și rezistenți la tăiere.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD COMPOUND
Tip	TL
Dimensiunea anvelopei	24.00 R 35
LI/SS	212 B

Dimensiuni US Standard

Usa code	94063819
TMPH	267
Overall Width (inch)	26
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.5
Rolling Circumference (inch)	259.7
Rim Rec	17.00/3.5
Rim Alt	---
Star Rating	***
TRA Code	E4

Load capacity (lbs)

mph / psi	105	109	112	116
30	41900	42500	43000	44100

Imprimat pe 4/18/2024 6:45 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..