

## EARTHMAX SR 45 PLUS - Specificații tehnice



### Descriere

EARTHMAX SR 45 PLUS este o anvelopă radială cu structură din oțel special concepută pentru camioanele de transport rigide. Este ideală pentru operațiuni pe distanțe lungi. Modelul benzii de rulare al anvelopei EARTHMAX SR 45 PLUS minimizează vibrațiile și zgomotul.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	27.00 R 49
LI/SS	223 B

## Dimensiuni Standard internațional

TKPH	440
Overall Width (mm)	746
Overall Diameter (mm)	2702
Static Loaded Radius (mm)	1214
Rolling Circumference (mm)	8095
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Imprimat pe 9/26/2023 7:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..