

EARTHMAX SR 45 PLUS - Specificații tehnice



Descriere

EARTHMAX SR 45 PLUS este o anvelopă radială cu structură din oțel special concepută pentru camioanele de transport rigide. Este ideală pentru operațiuni pe distanțe lungi. Modelul benzii de rulare al anvelopei EARTHMAX SR 45 PLUS minimizează vibrațiile și zgomotul.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD COMPOUND
Tip	TL
Dimensiunea anvelopei	27.00 R 49
LI/SS	223 B

Dimensiuni US Standard

Usa code	94049806
TMPH	370
Overall Width (inch)	29.4
Overall Diameter (inch)	106.4
Static Loaded Radius (inch)	47.8
Rolling Circumference (inch)	318.7
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Imprimat pe 4/26/2024 11:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..