

EARTHMAX SR 452 - Specificații tehnice



Descriere

EARTHMAX SR 452 este o anvelopă radială cu structură din oțel special concepută pentru autobasculante rigide în operațiuni de transport. Modelul unic al benzii de rulare E-4 oferă o tracțiune excelentă și o rezistență excepțională la căldură, minimizând vibrațiile și zgomotul pentru a oferi manevrabilitate și confort optime. Carcasa și curelele puternice din oțel asigură stabilitate și rezistență excelente la tăieturi și perforări. EARTHMAX SR 452 are o muchie pătrată care maximizează contactul cu solul pentru o manevrabilitate excelentă.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD COMPOUND
Tip	TL
Dimensiunea anvelopei	24.00 R 35
LI/SS	209 B

Dimensiuni Standard internațional

TKPH	415
Overall Width (mm)	660
Overall Diameter (mm)	2170
Static Loaded Radius (mm)	995
Rolling Circumference (mm)	6729
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Imprimat pe 12/5/2023 7:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..