

## EARTHMAX SR 454 - Specificații tehnice



### Descriere

EARTHMAX SR 454 este o anvelopă radială cu structură din oțel special concepută pentru basculante rigide. Designul unic al benzii de rulare E-3 și canelura centrală specială oferă tracțiuni laterale îmbunătățite și manevrabilitate atât pe suprafețe moi, cât și pe suprafețe noroioase. Această anvelopă este special concepută pentru viteze mai mari, curse lungi la temperatură de funcționare mai scăzută. Construcția din oțel având curele de oțel cu straturi multiple oferă o protecție superioară împotriva șocurilor și penetrării pietrelor, pentru a îmbunătăți timpul de funcționare pentru o productivitate mai mare. Muchia pătrată a anvelopei EARTHMAX SR 454 maximizează contactul cu solul pentru o manevrabilitate și stabilitate excelente și minimizează vibrațiile și zgomotul.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	27.00 R 49
LI/SS	223 B

## Dimensiuni Standard internațional

TKPH	525
Overall Width (mm)	740
Overall Diameter (mm)	2650
Static Loaded Radius (mm)	1187
Rolling Circumference (mm)	8040
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Imprimat pe 4/22/2024 7:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..