

EARTHMAX SR 454 - Specificații tehnice



Descriere

EARTHMAX SR 454 este o anvelopă radială cu structură din oțel special concepută pentru basculante rigide. Designul unic al benzii de rulare E-3 și canelura centrală specială oferă tracțiuni laterale îmbunătățite și manevrabilitate atât pe suprafețe moi, cât și pe suprafețe noroioase. Această anvelopă este special concepută pentru viteze mai mari, curse lungi la temperatură de funcționare mai scăzută. Construcția din oțel având curele de oțel cu straturi multiple oferă o protecție superioară împotriva șocurilor și penetrării pietrelor, pentru a îmbunătăți timpul de funcționare pentru o productivitate mai mare. Muchia pătrată a anvelopei EARTHMAX SR 454 maximizează contactul cu solul pentru o manevrabilitate și stabilitate excelente și minimizează vibrațiile și zgomotul.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	HEAT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	27.00 R 49
LI/SS	223 B

Dimensiuni US Standard

Usa code	94067794
TMPH	497
Overall Width (inch)	29.1
Overall Diameter (inch)	104.3
Static Loaded Radius (inch)	46.7
Rolling Circumference (inch)	316.5
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Imprimat pe 4/22/2024 6:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..