

## EARTHMAX SR 468 - Specificații tehnice



### Descriere

EARTHMAX SR 468 este o anvelopă radială cu structură din oțel special concepută pentru camioanele de transport rigide. Designul unic al benzii de rulare și compoziții speciali ai benzii de rulare o fac perfectă pentru condiții miniere dure, stâncoase și dificile. Blocurile sale cu caneluri circumferențiale și blocuri întrepătrunse asigură o disipare eficientă a căldurii. De asemenea, muchia pătrată robustă ajută la ejectarea pietrelor pentru a proteja anvelopa de deteriorări. EARTHMAX SR 468 este dezvoltată folosind tehnologia de ultimă oră de la BKT pentru a transporta sarcini grele, pentru a oferi o durată de viață mai lungă și pentru a oferi și rezistență la tăierea și perforarea cauzate de pietre.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD COMPOUND
Tip	TL
Dimensiunea anvelopei	40.00 R 57
LI/SS	250 B

## Dimensiuni Standard internațional

TKPH	950
Overall Width (mm)	1125
Overall Diameter (mm)	3575
Static Loaded Radius (mm)	1595
Rolling Circumference (mm)	10700
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	50000	51500	53000	54500	56000	58000	60000

Imprimat pe 4/20/2024 4:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..