

# EARTHMAX SR 47 TP - Specificații tehnice

## Descriere

EARTHMAX SR 47 TP (E-4) este o anvelopă radială cu structură din oțel, special proiectată pentru camioane de transport rigide care operează în condiții ce necesită tracțiune maximă și rezistență la și perforare. Adâncimea benzii de rulare a E-4 asigură uzura pe termen lung, chiar și pe distanțe mari, reducând astfel timpii de inactivitate și sporind productivitatea. Anvelopa EARTHMAX SR 47 TP este perfectă pentru orice sarcină care necesită atât tracțiune, cât și stabilitate, în special pe teren noroios sau alunecos. Disponibilă ca model standard și cu compoziți rezistenți la tăieturi.

## UM

Standard internațional

## Construcție



RADIAL

## Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD COMPOUND
Tip	TL
Dimensiunea anvelopei	24.00 R 35
LI/SS	209 B

## Dimensiuni Standard internațional

TKPH	440
Overall Width (mm)	650
Overall Diameter (mm)	2185
Static Loaded Radius (mm)	985
Rolling Circumference (mm)	6625
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Imprimat pe 5/4/2024 9:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..