

EARTHMAX SR 475 - Fișa de date



Descriere

EARTHMAX SR 475 este o anvelopă radială cu structură din oțel special concepută pentru autobasculante rigide. Este ideală pentru operațiuni în condiții foarte dificile pe teren stâncos, în special în transport pe distanțe mari. Designul unic al benzii de rulare generează căldură mai mică în zonele cu climă caldă și oferă o tracțiune excelentă. Carcasa și curelele sale puternice din oțel oferă o stabilitate deosebită și rezistență la rupturi și perforări. EARTHMAX SR 475 a fost dezvoltată cu muchie pătrată care asigură manevrabilitate și manipulare excelente, maximizând contactul cu solul.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
18.00 R 33	CUT RESISTANT COMPOUND	94064397	E4	**	191 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	182
18.00 R 33	CUT RESISTANT COMPOUND	94064854	E4	***	195 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	182
18.00 R 33	STANDARD COMPOUND	94064861	E4	***	195 B	13.00/2.5		19.3	73.2	33.9	225.2	TL	200
24.00 R 35	CUT RESISTANT COMPOUND	94066933	E4	**	209 B	17.00/3.5		25.7	85	38.2	259.4	TL	243
24.00 R 35	STANDARD COMPOUND	94066940	E4	**	209 B	17.00/3.5		25.7	85	38.2	259.4	TL	289

Imprimat pe 4/23/2024 11:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..