

EARTHMAX SR 47 - Specificații tehnice



Descriere

EARTHMAX SR 47 (E-4) este o anvelopă radială **cu structură din oțel** special concepută pentru camioanele de transport rigide care funcționează în condiții care necesită rezistență maximă la tăiere și perforare cauzate de pietre. Adâncimea benzii de rulare E-4 și designul unic al benzii de rulare asigură o uzură lungă chiar și pe distanțe lungi, reducând astfel timpul de nefuncționare și crescând productivitatea. Disponibilă în versiunea cu compuși standard și rezistenți la tăiere.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD COMPOUND
Tip	TL
Dimensiunea anvelopei	18.00 R 33
LI/SS	191 B

Dimensiuni Standard internațional

TKPH	204
Overall Width (mm)	510
Overall Diameter (mm)	1885
Static Loaded Radius (mm)	867
Rolling Circumference (mm)	5674
Rim Rec	13.00/2.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

Imprimat pe 4/14/2024 6:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..