

## EARTHMAX SR 484 - Specificații tehnice



### Descriere

EARTHMAX SR 484 este o anvelopă radială cu structură din oțel special concepută pentru basculante rigide pentru transport în aplicații miniere de suprafață. Are un design unic al benzii de rulare E-3 cu un compus special al benzii de rulare care asigură o protecție excelentă în condiții dure și stâncoase, împreună cu tracțiune îmbunătățită și proprietăți excelente de auto-curățare. Construcția sa din oțel și curelele de oțel cu straturi multiple oferă o protecție superioară împotriva șocurilor, oboselii și găurile cauzate de pietre, crescând timpul de funcționare și creșterea productivității. EARTHMAX SR 484 are un design cu muchie pătrată, care maximizează contactul cu solul pentru o manevrabilitate și stabilitate excelente. Această anvelopă BKT este special concepută pentru viteze mai mari și curse lungi.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	27.00 R 49
LI/SS	223 B

## Dimensiuni Standard internațional

TKPH	525
Overall Width (mm)	735
Overall Diameter (mm)	2647
Static Loaded Radius (mm)	1193
Rolling Circumference (mm)	8055
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Imprimat pe 4/27/2024 8:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..