

EARTHMAX SR 484 - Specificații tehnice



Descriere

EARTHMAX SR 484 este o anvelopă radială cu structură din oțel special concepută pentru basculante rigide pentru transport în aplicații miniere de suprafață. Are un design unic al benzii de rulare E-3 cu un compus special al benzii de rulare care asigură o protecție excelentă în condiții dure și stâncoase, împreună cu tracțiune îmbunătățită și proprietăți excelente de auto-curățare. Construcția sa din oțel și curelele de oțel cu straturi multiple oferă o protecție superioară împotriva șocurilor, oboselii și găurile cauzate de pietre, crescând timpul de funcționare și creșterea productivității. EARTHMAX SR 484 are un design cu muchie pătrată, care maximizează contactul cu solul pentru o manevrabilitate și stabilitate excelente. Această anvelopă BKT este special concepută pentru viteze mai mari și curse lungi.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	27.00 R 49
LI/SS	223 B

Dimensiuni US Standard

Usa code	94067817
TMPH	360
Overall Width (inch)	28.9
Overall Diameter (inch)	104.2
Static Loaded Radius (inch)	47
Rolling Circumference (inch)	317.1
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Imprimat pe 4/27/2024 10:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..