

## EARTHMAX SR 49 M - Specificații tehnice



### Descriere

EARTHMAX SR 49 M este o anvelopă radială cu structură din oțel cu un model nedirecțional special, concepută pentru benzile de transport de încărcare (LHD), basculante cu profil redus (LPDT), încărcătoare și buldozere care funcționează în condiții stâncoase severe, în principal în minerit subteran. EARTHMAX SR 49 M este ideală pentru operațiuni foarte dificile care necesită tracțiune și stabilitate excepționale. Banda de rulare adâncă L-4 și compusul special formulat UMS (pentru mine subterane) asigură o uzură mai lungă a benzii de rulare, în plus față de rezistența excelentă la tăieturi și perforări cauzate de roci.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

OTR: Buldozer • Basculare încărcături (LHD) • Încărcător • Autobasculantă cu profil redus (LPDT)

Versiune

CUT RESISTANT COMPOUND (UMS)

Tip

TL

Dimensiunea anvelopei

29.5 R 29

## Dimensiuni US Standard

Usa code	94058648
Overall Width (inch)	30.9
Overall Diameter (inch)	79
Static Loaded Radius (inch)	35.7
Rolling Circumference (inch)	248.8
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5, 26.00/3.5
Star Rating	****
TRA Code	E4

## Load capacity (lbs)

\* "consult your servicing dealer or BKT representative for speed, load and pressure details."

Imprimat pe 4/23/2024 9:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..