

EARTHMAX SR 50 - Specificații tehnice



Descriere

EARTHMAX SR 50 (L-5) este o anvelopă radială **cu structură din oțel** special concepută pentru încărcătoare. Carcasa durabilă și protecțiile laterale sunt ideale pentru cele mai solicitante operațiuni. EARTHMAX SR 50 este fabricată dintr-un compus special rezistent la tăiere, care asigură o durată lungă de viață. Operatorii vor aprecia, de asemenea, tracțiunea excelentă, stabilitatea și deplasarea confortabilă.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	26.5 R 25
LI/SS	202 A2

Dimensiuni US Standard

Usa code	94032303
Overall Width (inch)	27.2
Overall Diameter (inch)	69.8
Static Loaded Radius (inch)	31.7
Rolling Circumference (inch)	210
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	28300	29100	30900	32000	33100

Imprimat pe 4/27/2024 12:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..