

## EARTHMAX SR 51 - Specificații tehnice



### Descriere

EARTHMAX SR 51 (L-5) este o anvelopă radială cu structură din oțel special concepută pentru încărcătoare sau buldozere. EARTHMAX SR 51 este ideală pentru operațiuni în condiții dificile, care necesită rezistență suplimentară la tăiere, protecție laterală și tracțiune excepțională. &nbsp;

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

OTR: Buldozer • Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	23.5 R 25
LI/SS	195 A2

## Dimensiuni Standard internațional

Overall Width (mm)	612
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	743
Rolling Circumference (mm)	4882
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L5

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	10300	10600	11200	11500	12150

Imprimat pe 3/4/2024 3:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..