

EARTHMAX SR 51 - Specificații tehnice



Descriere

EARTHMAX SR 51 (L-5) este o anvelopă radială **cu structură din oțel** special concepută pentru încărcătoare sau buldozere. EARTHMAX SR 51 este ideală pentru operațiuni în condiții dificile, care necesită rezistență suplimentară la tăiere, protecție laterală și tracțiune excepțională.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Buldozer • Încărcător

| | |
|-----------------------|------------------------|
| Versiune | CUT RESISTANT COMPOUND |
| Tip | TL |
| Dimensiunea anvelopei | 35/65 R 33 |
| LI/SS | 229 A2 |

Dimensiuni US Standard

| | |
|------------------------------|-----------|
| Usa code | 94069866 |
| Overall Width (inch) | 35.6 |
| Overall Diameter (inch) | 81.1 |
| Static Loaded Radius (inch) | 34.3 |
| Rolling Circumference (inch) | 239.4 |
| Rim Rec | 28.00/3.5 |
| Star Rating | *** |
| TRA Code | L5 |

Load capacity (lbs)

| mph / psi | 98 | 102 | 105 | 109 | 112 | 116 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 64000 | 66000 | 68000 | 69500 | 70500 | 71500 |

Imprimat pe 4/23/2024 9:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..