

EARTHMAX SR 57 - Specificații tehnice



Descriere

EARTHMAX SR 57 este o anvelopă radială cu structură din oțel special concepută pentru încărcătoare, buldozere și vehicule utilitare care operează în minele subterane. Anvelopa oferă tracțiune, stabilitate și confort superioare pe suprafețe dificile și stâncoase. Banda de rulare L-5 extra adâncă și compusul special formulat UMS (pentru mine subterane) asigură o uzură mai lungă a benzii de rulare, pe lângă rezistența extraordinară la tăieturi și perforări cauzate de roci.

UM

US Standard

Construcție

 RADIAL

Mașinării

OTR: Buldozer • Basculare încărcături (LHD) • Încărcător

Versiune	CUT RESISTANT COMPOUND
Tip	TT
Dimensiunea anvelopei	12.00 R 20

Dimensiuni US Standard

Usa code	94057160
Overall Width (inch)	12.5
Overall Diameter (inch)	46.5
Rim Rec	8.50
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	102
3.7	11460

Imprimat pe 4/23/2024 11:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..