

EM 933 SUPER - Specificații tehnice



Descriere

EM 933 SUPER a fost proiectat special pentru excavatoarele ce execută lucrări de săpare și încărcare. Designul remarcabil al pereților laterali, cu o muchie proeminentă ce permite contactul strâns între două anvelope eliminând nevoia unui inel special din cauciuc pentru a preveni pătrunderea pietrelor. Designul unic al benzii de rulare oferă o tracțiune superioară în situații de servicii pentru condiții grele de lucru. Caracteristicile suplimentare ale EM 933 SUPER sunt un confort ridicat la rulare și proprietăți de auto-curățare îmbunătățite.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Excavator

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	290/90 - 20
LI/SS	152 B / 168 A2

Dimensiuni Standard internațional

Rating de sarcină	18
Overall Width (mm)	295
Overall Diameter (mm)	1055
Rim Rec	8.00
TRA Code	E2

Load capacity (Kg)

km/h / bar	9.00
10	5600
50	3530

Imprimat pe 4/28/2024 10:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..