

## EM 934 - Specificații tehnice



### Descriere

EM 934 a fost special concepută pentru excavatoare în aplicații de construcție de drumuri. Prezintă o tracțiune laterală excelentă, precum și caracteristici remarcabile de auto-curățare. Compusul unic al benzii de rulare oferă rezistență la tăiere și așchiere, în timp ce carcasa puternică oferă o durată de viață lungă. &nbsp;&nbsp;&nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Industrial: Excavator

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	10.00 - 20
LI/SS	146 B

## Dimensiuni US Standard

Usa code	94048601
Rating de sarcină	16
Overall Width (inch)	11
Overall Diameter (inch)	41.7
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	126.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

## Load capacity (lbs)

mph / psi	109
30	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/13/2025 3:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..