

EM 937 E3 (L) - Specificații tehnice



Descriere

EM 937 (E-3/L-3) a fost special concepută pentru încărcătoare și buldoexcavatoare în aplicații de săpat și încărcare, în funcție de dimensiune. Are o durabilitate excelentă și oferă rezistență la tăiere și așchiere.

UM

US Standard

Construcție

 BIAS

Mașinării

Industrial: Buldoexcavator • Încărcător

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	14.00 - 25

Dimensiuni US Standard

Usa code	94015399
Rating de sarcină	20
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	161.6
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	69	102
30	10200	-
5	-	18700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 12/8/2024 10:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..