

EM 937 (E3) - Specificații tehnice



Descriere

EM 937 (E-3) a fost special concepută pentru basculante rigide în aplicații miniere de suprafață. Are o durabilitate excelentă și oferă rezistență ridicată la tăiere și așchiere. EM 937 (E-3) este potrivită în special pentru lucrări în condiții dificile.

UM

Standard internațional

Construcție

 BIAS

Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	14.00 - 25

Dimensiuni Standard internațional

Rating de sarcină	28
Overall Width (mm)	375
Overall Diameter (mm)	1368
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4105
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load capacity (Kg)

km/h / bar	6.50	9.25
50	5600	-
10	-	10000

Imprimat pe 12/2/2023 12:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..