

EM 937 (E3) - Fișa de date



Descriere

EM 937 (E-3) a fost special concepută pentru basculante rigide în aplicații miniere de suprafață. Are o durabilitate excelentă și oferă rezistență ridicată la tăiere și așchiere. EM 937 (E-3) este potrivită în special pentru lucrări în condiții dificile.

UM

Standard internațional

Construcție

✚ BIAS

Mașinării

OTR: Autobasculantă rigidă

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	E3/L3	28	10.00/1.5		375	1368	620	4105	TT
14.00 - 25	STANDARD	E3/L3	28	10.00/1.5		375	1368	620	4105	TL

Imprimat pe 4/19/2024 3:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..