

FARM 2000 - Specificații tehnice



Descriere

Anvelopa FARM 2000 este potrivită pe tractoare pentru aplicații de prelucrare a solului. A fost proiectată cu un compus special rezistent la tăiere și așchiere pentru a asigura o durabilitate mai bună. Datorită carcasei sale puternice, FARM 2000 oferă o capacitate mare de încărcare. De asemenea, oferă proprietăți excelente de tracțiune și auto-curățare.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Tractor

Versiune	HD
Tip	TT
Dimensiunea anvelopei	16.9 - 28
LI/SS	135 A6

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	429
Overall Diameter (mm)	1420
Static Loaded Radius (mm)	657
Rolling Circumference (mm)	4351
SRI (mm)	675
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004378
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.70
30	2180

Imprimat pe 5/11/2024 3:10 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..