

## FARM 2000 - Specificații tehnice



### Descriere

Anvelopa FARM 2000 este potrivită pe tractoare pentru aplicații de prelucrare a solului. A fost proiectată cu un compus special rezistent la tăiere și așchiere pentru a asigura o durabilitate mai bună. Datorită carcasei sale puternice, FARM 2000 oferă o capacitate mare de încărcare. De asemenea, oferă proprietăți excelente de tracțiune și auto-curățare.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

## Dimensiuni Standard internațional

Lățimea secțiunii (mm)	265
Overall Diameter (mm)	775
Static Loaded Radius (mm)	349
Rolling Circumference (mm)	2294
SRI (mm)	360
Rim Rec	9.00
ECE	E11-106R-003516

## Load capacity (Kg)

km/h / bar	3.60
10 FR	2380
25 FR	2025
30 FR	1905
40 FR	1700
10 DW	1650
25 DW	1405
30 DW	1320
40 DW	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 2/10/2025 5:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..